40 CFR Ch. I (7-1-06 Edition)

PSES

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million of lead pro- smelting
Antimony Arsenic Lead Zinc Ammonia (as N)	.247 .178 .036 .131	.110 .073 .017 .054

§421.136 Pretreatment standards for new sources.

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources. The mass of wastewater pollutants in secondary lead process wastewater introduced into a POTW shall not exceed the following values:

(a) Subpart M—Battery Cracking.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pound pounds) of produced	ds per million f lead scrap
Antimony Arsenic	1.299 .936	.579 .384 .087
Zinc	.189 .687 .000	.283 .000

(b) Subpart M—Blast, Reverberatory, or Rotary Furnace Wet Air Pollution Control.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millior pounds) of lead pro duced from smelting	
Antimony	5.038 3.628 .731 2.662 .000	2.245 1.488 .339 1.096

(c) Subpart M—Kettle Wet Air Pollution Control.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead produced from refining	
Antimony	.000 .000 .000 .000	.000 .000 .000 .000

 $\begin{array}{ccc} \text{(d)} & \text{Subpart} & \text{M--Lead} & \text{Paste} \\ \text{Desulfurization.} \end{array}$

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millio pounds) of lead pro- essed throug desulfurization	
Antimony	.000 .000 .000 .000	.000 .000 .000 .000

(e) Subpart M—Casting Contact Cooling.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million f lead cast
Antimony Arsenic Lead Zinc Ammonia (as N)	.042 .031 .006 .022 .000	.019 .013 .003 .009

(f) Subpart M—Truck Wash.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead pro- duced from smelting	
Antimony	.041 .029 .006 .021	.018 .012 .003 .009

(g) Subpart M—Facility Washdown.

Environmental Protection Agency

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead pro duced from smelting	
Antimony	.000 .000 .000 .000	.000 .000 .000 .000

(h) Subpart M—Battery Case Classification.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
		ds per million f lead scrap
Antimony	.000 .000 .000 .000	.000 .000 .000 .000

(i) Subpart M—Employee Handwash.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead pro duced from smelting	
Antimony	.052 .038 .008 .028 .000	.023 .015 .004 .011

(j) Subpart M—Employee Respirator Wash.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per millio pounds) of lead pro duced from smelting	
Antimony	.085 .061 .012 .045	.038 .025 .006 .018

(k) Subpart M—Laundering of Uniforms.

PSNS

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of lead pro duced from smelting	
Antimony	.247 .178 .036 .131	.110 .073 .017 .054

§421.137 [Reserved]

Subpart N—Primary Antimony Subcategory

Source: 50 FR 38345, Sept. 20, 1985, unless otherwise noted.

§ 421.140 Applicability: Description of the primary antimony subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of antimony at primary antimony facilities.

§421.141 Specialized definitions.

For the purpose of this subpart the general definitions, abbreviations, and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

§ 421.142 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available:

(a) Sodium Antimonate Autoclave Wastewater.